Intellinet NFD30 Network Dome Camera MPEG4 Motion-JPEG Dual Mode PoE Audio (

Location **Gauteng, Centurion** https://www.freeadsz.co.za/x-133929-z



Intellinet NFD30 Network Dome Camera MPEG4 + Motion-JPEG Dual Mode PoE Audio - Excellent image quality with 30 fps full-motion video in all resolutions Progressive-scan image sensor with OmniPixel2 technology Supports image resolutions up to 640 x 480 (VGA) Audio support, full duplex, up to 8 kHz, with integrated microphone 3.7 â€" 12 mm, F1.4 vari-focal lens Video access through any standard Web browser Integrated motion detection with pre- and post-alarm image/video buffering Eventtriggered FTP and e-mail upload of still images and videos Terminal block for external sensors or external alarm devices Supports simultaneous MPEG4 and Motion-JPEG image compression Supports MPEG4 video streaming with CBR (constant bit rate) and VBR (variable bit rate) modes Supports low light conditions, minimum 0.5 lux Mobile phone streaming live video through 3GPP / ISMA / RTSP Mobile phone live image through 2.5 WAP MPEG4 + Motion-JPEG + 3GPP mobile phone streaming, audio and 10x digital zoom, Retail Box, 3 Year Warranty



The Intellinet NFD30 Network Dome Camera is designed for security surveillance applications, and comes fully equipped with state-of-the-art features that set it apart from other network cameras on the market today.

Excellent Video Quality

Because the NFD30 Network Dome Camera uses a progressive-scan CMOS sensor, it provides sharp








































superior quality and, at the same time, continuing to support existing applications. MPEG4, on the other hand, allows you to transmit a larger amount of data over the same amount of bandwidth while providing smooth and seamless viewing.

Bi-Directional Audio Support

Attaching a microphone and loudspeakers to the NFD30 Network Dome Camera will allow you to listen and talk using the two-way audio support. On top of that, the camera is equipped with an internal microphone. This is ideal for most security and surveillance applications.

Integrated DDNS Client

Utilize the free DYNDNS service (like DYNDNS.org) in order to connect to your camera, even if you do not have a static IP address assigned by your ISP (Internet service provider). This feature lets you easily set up a URL that can be used to access the camera through the Internet using any Web browser.

Power over Ethernet

The NFD30 Network Dome Camera supports the 802.3af standard, allowing it to be installed in locations where an AC power source is not readily available. Simply plug the camera into a PoE-compliant switch and begin transmitting power as well as data over the Cat5e or Cat6 network