

Dell X1018 Websmart Switch - Brandnew Sealed X-SERIES Rack Mount (1700 R)



Location **Gauteng, Johannesburg**
<https://www.freeadsz.co.za/x-161061-z>

GENERAL

Subtype Gigabit Ethernet
 Ports 16 x 10/100/1000 + 2 x Gigabit SFP
 Capacity MAC addresses : 16000
 LAG groups : 12
 Priority queues per port : 4
 Virtual interfaces (VLANs) : 4096
 Maximum member ports per LAG : 8
 Authentication Method RADIUS, TACACS+
 MAC Address Table Size 16K entries
 Authentication Method RADIUS, TACACS+
 Manufacturer Dell, Inc.











NETWORKING

MAC Address Table Size 16K entries
 Subcategory network hubs and switches
 Subtype Gigabit Ethernet
 Form Factor rack-mountable
 Type switch
 Advanced Switching Layer 2+
 Features ARP inspection, Head of Line Blocking Prevention, IPv6 support, LLDP support, Link

Aggregation Control Protocol (LACP), MLD snooping, Multiple Spanning Tree Protocol (MSTP) support, Equal Cost Multi Path (ECMP), Quality of Service (QoS), RSTP, Spanning Tree Protocol (STP), STP support, Access Control List (ACL), Syslog, SNMP, DHCP support, Spanning Tree Protocol (STP) support, System Time, Trivial File Transfer Protocol (TFTP) support, External Link Aggregation (DLDP), Port Security, Virtual Port Channel (VPC) technology, auto configuration, port mirroring, Back Pressure Support, static routing, Broadcast Storm Control, DHCP relay, DHCP server, DHCP snooping, DNS server, GARP, VLAN Registration Protocol (VVRP), GVRP, IEEE 802.1D, IEEE 802.3ad (LACP), IEEE 802.3x, IEEE 802.1Q, IEEE 802.1ab (LLDP), IEEE 802.1p, IEEE 802.1s, IEEE 802.1v, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ac

Ports Qty 16
 Managed Yes
 Remote Management Protocol CLI, HTTP, RMON, SNMP 1, SNMP 2, SNMP 3



 https://www.freeadsz.co.za/x-1610 Dell X1018 Websmart Switch - Brandnew Sealed X-SERIES Rack Mount	 https://www.freeadsz.co.za/x-1610 Dell X1018 Websmart Switch - Brandnew Sealed X-SERIES Rack Mount	 https://www.freeadsz.co.za/x-1610 Dell X1018 Websmart Switch - Brandnew Sealed X-SERIES Rack Mount	 https://www.freeadsz.co.za/x-1610 Dell X1018 Websmart Switch - Brandnew Sealed X-SERIES Rack Mount	 https://www.freeadsz.co.za/x-1610 Dell X1018 Websmart Switch - Brandnew Sealed X-SERIES Rack Mount	 https://www.freeadsz.co.za/x-1610 Dell X1018 Websmart Switch - Brandnew Sealed X-SERIES Rack Mount	 https://www.freeadsz.co.za/x-1610 Dell X1018 Websmart Switch - Brandnew Sealed X-SERIES Rack Mount	 https://www.freeadsz.co.za/x-1610 Dell X1018 Websmart Switch - Brandnew Sealed X-SERIES Rack Mount	 https://www.freeadsz.co.za/x-1610 Dell X1018 Websmart Switch - Brandnew Sealed X-SERIES Rack Mount	 https://www.freeadsz.co.za/x-1610 Dell X1018 Websmart Switch - Brandnew Sealed X-SERIES Rack Mount
---	--	--	--	---	--	--	--	--	--

POWER DEVICE

Power Provided 40 Watt

Nominal Voltage AC 120/230 V

Frequency Required 50/60 Hz

Power Consumption Operational 21.5 Watt

Type internal power supply

INTERFACE PROVIDED

Qty 1, 16, 2

Comments management

MISCELLANEOUS

Color Category black

Height (Rack Units) 1 m

ENVIRONMENTAL PARAMETERS

Min Operating Temperature 32 °F

Max Operating Temperature 113 °F

Min Storage Temperature -4 °F

Max Storage Temperature 158 °F

Humidity Range Operating 10 - 90% (non-condensing)

HEADER

Brand