

Weather Proof Outdoor Dual PIR detector Motion Sensor with Pet-immune Function (

Sensor with Ture Motion



Location **Gauteng, Pretoria**
<https://www.freeadsz.co.za/x-196845-z>



DG-85 is a kind of PIR intrusion detector integrating the most advanced security technology. It adopts 2 dual PIR sensors with high accuracy, intelligent digital chip, advanced, of ware technology, which can help it to make an accurate judgment of true intruder or other interference that can cause wrong alarm. And it is with function of automatic memory of environmental change, which can avoid wrong alarm caused by hot & cold air, operation machine interference. It can prevent effectively the interference caused by a 25kg past or 10 cats, insect, mouse, birds etc. Its super filter can be used indoor and outdoor. This has clear various interference that common PIR detector can't overcome; and put an end to wrong alarm and miss alarm.

Specifications:

Input Voltage: 9 to 16V DC
 Current Drain: 30mA 12V DC
 Detecting Range: 11.6m * 11.6m
 Detecting Angle: 90 degree
 Alarm output: NC > 100MA/28V DC
 Anti white light resistance: >20000LUX
 Installation height: 2m to 2.7m
 Tamper switch: NC. 100mA/20V DC
 PIR Section: Lens Date

No. of curtain Beams $(11+11+9) * 2 = 62$

Location

Alarm delay time: 10 to 60 seconds

Working voltage: 10V to 16V DC, 1000mA

Motion test: 0.2m/s - 3.5m/s (0.6ft-11ft)

Environmental:

Operating Temp: -10 to 50 centi-grade

Humidity: 5% to 95% (RH)

Storage Temp: -20 to 60 centi-grade

Physical size: 176*55*69mm

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

No. of curtain Beams $(11+11+9) * 2 = 62$

Location

Alarm delay time: 10 to 60 seconds

Working voltage: 10V to 16V DC, 1000mA

Motion test: 0.2m/s - 3.5m/s (0.6ft-11ft)

Environmental:

Operating Temp: -10 to 50 centi-grade

Humidity: 5% to 95% (RH)

Storage Temp: -20 to 60 centi-grade

Physical size: 176*55*69mm

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

No. of curtain Beams $(11+11+9) * 2 = 62$

Location

Alarm delay time: 10 to 60 seconds

Working voltage: 10V to 16V DC, 1000mA

Motion test: 0.2m/s - 3.5m/s (0.6ft-11ft)

Environmental:

Operating Temp: -10 to 50 centi-grade

Humidity: 5% to 95% (RH)

Storage Temp: -20 to 60 centi-grade

Physical size: 176*55*69mm

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

No. of curtain Beams $(11+11+9) * 2 = 62$

Location

Alarm delay time: 10 to 60 seconds

Working voltage: 10V to 16V DC, 1000mA

Motion test: 0.2m/s - 3.5m/s (0.6ft-11ft)

Environmental:

Operating Temp: -10 to 50 centi-grade

Humidity: 5% to 95% (RH)

Storage Temp: -20 to 60 centi-grade

Physical size: 176*55*69mm

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

No. of curtain Beams $(11+11+9) * 2 = 62$

Location

Alarm delay time: 10 to 60 seconds

Working voltage: 10V to 16V DC, 1000mA

Motion test: 0.2m/s - 3.5m/s (0.6ft-11ft)

Environmental:

Operating Temp: -10 to 50 centi-grade

Humidity: 5% to 95% (RH)

Storage Temp: -20 to 60 centi-grade

Physical size: 176*55*69mm

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

No. of curtain Beams $(11+11+9) * 2 = 62$

Location

Alarm delay time: 10 to 60 seconds

Working voltage: 10V to 16V DC, 1000mA

Motion test: 0.2m/s - 3.5m/s (0.6ft-11ft)

Environmental:

Operating Temp: -10 to 50 centi-grade

Humidity: 5% to 95% (RH)

Storage Temp: -20 to 60 centi-grade

Physical size: 176*55*69mm

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

No. of curtain Beams $(11+11+9) * 2 = 62$

Location

Alarm delay time: 10 to 60 seconds

Working voltage: 10V to 16V DC, 1000mA

Motion test: 0.2m/s - 3.5m/s (0.6ft-11ft)

Environmental:

Operating Temp: -10 to 50 centi-grade

Humidity: 5% to 95% (RH)

Storage Temp: -20 to 60 centi-grade

Physical size: 176*55*69mm

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

No. of curtain Beams $(11+11+9) * 2 = 62$

Location

Alarm delay time: 10 to 60 seconds

Working voltage: 10V to 16V DC, 1000mA

Motion test: 0.2m/s - 3.5m/s (0.6ft-11ft)

Environmental:

Operating Temp: -10 to 50 centi-grade

Humidity: 5% to 95% (RH)

Storage Temp: -20 to 60 centi-grade

Physical size: 176*55*69mm

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

No. of curtain Beams $(11+11+9) * 2 = 62$

Location

Alarm delay time: 10 to 60 seconds

Working voltage: 10V to 16V DC, 1000mA

Motion test: 0.2m/s - 3.5m/s (0.6ft-11ft)

Environmental:

Operating Temp: -10 to 50 centi-grade

Humidity: 5% to 95% (RH)

Storage Temp: -20 to 60 centi-grade

Physical size: 176*55*69mm

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

No. of curtain Beams $(11+11+9) * 2 = 62$

Location

Alarm delay time: 10 to 60 seconds

Working voltage: 10V to 16V DC, 1000mA

Motion test: 0.2m/s - 3.5m/s (0.6ft-11ft)

Environmental:

Operating Temp: -10 to 50 centi-grade

Humidity: 5% to 95% (RH)

Storage Temp: -20 to 60 centi-grade

Physical size: 176*55*69mm

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

No. of curtain Beams $(11+11+9) * 2 = 62$

Location

Alarm delay time: 10 to 60 seconds

Working voltage: 10V to 16V DC, 1000mA

Motion test: 0.2m/s - 3.5m/s (0.6ft-11ft)

Environmental:

Operating Temp: -10 to 50 centi-grade

Humidity: 5% to 95% (RH)

Storage Temp: -20 to 60 centi-grade

Physical size: 176*55*69mm

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

No. of curtain Beams $(11+11+9) * 2 = 62$

Location

Alarm delay time: 10 to 60 seconds

Working voltage: 10V to 16V DC, 1000mA

Motion test: 0.2m/s - 3.5m/s (0.6ft-11ft)

Environmental:

Operating Temp: -10 to 50 centi-grade

Humidity: 5% to 95% (RH)

Storage Temp: -20 to 60 centi-grade

Physical size: 176*55*69mm

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

No. of curtain Beams $(11+11+9) * 2 = 62$

Location

Alarm delay time: 10 to 60 seconds

Working voltage: 10V to 16V DC, 1000mA

Motion test: 0.2m/s - 3.5m/s (0.6ft-11ft)

Environmental:

Operating Temp: -10 to 50 centi-grade

Humidity: 5% to 95% (RH)

Storage Temp: -20 to 60 centi-grade

Physical size: 176*55*69mm

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

Freeadsz.co.za/x-196845-z

No. of curtain Beams $(11+11+9) * 2 = 62$

Location

Alarm delay time: 10 to 60 seconds

Working voltage: 10V to 16V DC, 1000mA

Motion test: 0.2m/s - 3.5m/s (0.6ft-11ft)

Environmental:

Operating Temp: -10 to 50 centi-grade

Package content:

1 x Wired PIR