YAMAHA HS7 2-WAY 6.5quot 95W ACTIVE STUDIO MONITOR R9995.00 PER PAIR NE





Location Gauteng, Johannesburg

https://www.freeadsz.co.za/x-206978-z

YAMAHA HS 7

R9995.00 PER PAIR

2-WAY BASS-REFLEX BI-AMPLIFIED NEARFIELD STUDIO MONITOR WITH 6.5" CONE.

THE YAMAHA HS7 IS A 2-WAY BASS-REFLEX BI-AMPLIFIED NEARFIELD STUDIO MONITOR WITH 6.5" CONE WOOFER AND 1" DOME TWEETER. THE YAMAHA HS-SERIES HAVE THE INHERITED UNIVERSAL MIX-TRANSLATION LEGACY AND DISTINCTIVE WHITE CONES OF THE INDUSTRY-RESPECTED NS-10'S, DESIGNED TO DELIVER YOUR MIXES WITH TRANSPARENT HONESTY. ROOM CONTROL AND FREQUENCY RESPONSE SWITCHES ALLOW CUSTOM TAILORING OF THE MONITOR'S RESPONSE TO GIVE YOU ACCURATE PERFORMANCE IN ANY ENVIRONMENT.

HIGH-PERFORMANCE SPEAKERS AND MOUNTING SYSTEM

THE ELEGANT WHITE-CONE SPEAKERS USED IN THE HS-SERIES MONITORS DELIVER SUPERLATIVE AUDIO PERFORMANCE THAT IS FURTHER ENHANCED BY A CAREFULLY ENGINEERED MOUNTING SYSTEM. A SYSTEM OF SCREWS AND A SPECIALLY DESIGNED MOUNTING RING ELIMINATES SPURIOUS VIBRATION AND RESONANCE, ALLOWING THE SPEAKER TO DELIVER ITS FULL SONIC POTENTIAL. ANOTHER FEATURE THAT BOOSTS WOOFER PERFORMANCE IS A MAGNET SELECTED TO PRODUCE ACCURATE, SOLID LOW-END









~ ==	
YAMAHA 6.5quot 95W	MONITOR PAIR https://www.fre 78-z
YAMAHA HS7 2-W. 6.5auot 95W ACTIVE STUD	MONITOR R9995.00 PI PAIR NE https://www.freeadsz.co.za/x-20 78-z



A IR N Eps://www.fr	SYAMAHA
ECONOMIC STUDENT OF THE STUDENT OF T	RHS7 2-





SYSTEM TYPE:ACTIVE

CONFIGURATION:2-WAY

DRIVERS

LOW-FREQUENCY DRIVER: 6.5"

MID-FREQUENCY DRIVER:NOT APPLICABLE

HIGH-FREQUENCY DRIVER: 1"

FULL-RANGE DRIVER:NOT APPLICABLE

DRIVER TYPE: INFO NOT AVAILABLE

SOUND

FREQUENCY RESPONSE: 43HZ â€" 30KHZ

MAX PEAK SPL: INFO NOT AVAILABLE

AMPLIFIER CLASS: INFO NOT AVAILABLE

OUTPUT POWER: 95W

ONBOARD FEATURES

INPUT CONNECTORS:XLR, TRS

STANDBY MODE: INFO NOT AVAILABLE

ACOUSTIC SPACE CONTROL:YES

POWER INDICATOR:YES

SPECIFICATIONS

HS7 POWERED STUDIO MONITOR

SPEAKER TYPE 2-WAY BI-AMP POWERED STUDIO MONITOR
FREQUENCY RANGE (-10DB) 43HZ - 30KHZ
COMPONENTS LF 6.5" CONE
HF 1" DOME
CROSSOVER 2KHZ
OUTPUT POWER 95W (LF:60W, HF:35W)
I/O CONNECTORS XLR3-31 TYPE (BALANCED), PHONE (BALANCED)
POWER CONSUMPTION 55W
SHAPE BASS-REFLEX TYPE
CABINET MATERIAL