

Ebara AGA15060M (10602 R)



Location **Gauteng, Moot**
<https://www.freedasz.co.za/x-9585-z>

APPLICATIONS

- Domestic pressure boosting
- Small-scale garden irrigation
- Washing vehicles
- Moving clean water in general

TECHNICAL DETAILS

• AGA 0.60 - 0.75 also available in "GARDEN" versions i.e. GARDEN (with handle, standard socket and 1.5 m cable) and "GL" (with handle, standard socket and 1.5 m cable and switch)



• Available with brass impeller (AGA 0.60 M GO, AGA 0.75 M GO, AGA 1.00 M GO)

TECHNICAL DATA

- Maximum working pressure:
 - 6 bar for AGA 0.60-0.75-1.00
 - 10 bar for the rest of the range
- Maximum temperature of the liquid: 45°C
- Maximum suction depth: 8 m
- Self-ventilated 2 pole asynchronous motor
- Class of insulation F
- IP44 Protection rating

- 230V $\pm 10\%$, 50Hz single phase voltage
- 30/400VA, 50Hz transformer voltage
- 50/60Hz capacitor motor and the metric base with automatic incorporation of the single phase motor
- 100% duty under use
- G1 suction connection for AGA 0.60-0.75-1.00, G1A, 1/2 for the rest of the range
- G1 discharge connection

- Cast iron pump body
- Seal housing disc AISI 304 for AGA 0.60-0.75-1.00, in brass for the rest of the range

 https://www.freedasz.co.za/x-9585-z Ebara AGA15060M	 https://www.freedasz.co.za/x-9585-z Ebara AGA15060M	 https://www.freedasz.co.za/x-9585-z Ebara AGA15060M	 https://www.freedasz.co.za/x-9585-z Ebara AGA15060M	 https://www.freedasz.co.za/x-9585-z Ebara AGA15060M	 https://www.freedasz.co.za/x-9585-z Ebara AGA15060M	 https://www.freedasz.co.za/x-9585-z Ebara AGA15060M	 https://www.freedasz.co.za/x-9585-z Ebara AGA15060M	 https://www.freedasz.co.za/x-9585-z Ebara AGA15060M	 https://www.freedasz.co.za/x-9585-z Ebara AGA15060M
---	--	--	--	---	--	--	--	--	--

• Shaft in AISI 416 for AGA 0.60-0.75-1.00, in AISI 303 for the rest of the range

• Impeller in PPO reinforced with fibreglass for AGA 0.60-0.75-1.00, in brass for the rest of the range

• Mechanical seal in Carbon/Ceramic/NBR

• Ejector and nozzle in PPO reinforced with