

Shimge QB80 0.75kw 230V Peripheral Pump (1300 R)



Location **Gauteng, Moot**
<https://www.freeadsz.co.za/x-9586-z>

Shimge QB80 0.75kw 230V Peripheral Pump

Application

Clean water without abrasive particles, non-aggressive liquid.

Perfect for domestic use.

In particular for delivering water in combination with small pressure sets and for irrigation.

Installed in enclosed places, or at least protected against inclement weather.

Operation Conditions

Suction lift up to 8M.

Liquid temperature up to +40°C.

Ambient temperature up to +40°C.

Max. working pressure 6 Bar.

Motor

2-pole induction motor: 50Hz.

Insulation: Class B.

Protection: IP 44.

With capacitor and thermal overload protection

Cast iron
 Housing: Aluminum
 Impeller: Brass
 Shaft with motor: Stainless steel
 Mechanical seal: Ceramic Graphite.
 Copper



Shimge QB80 0.75kw 230V
 Peripheral Pump

<https://www.freeadsz.co.za/x-9586-z>



Shimge QB80 0.75kw 230V
 Peripheral Pump

<https://www.freeadsz.co.za/x-9586-z>



Shimge QB80 0.75kw 230V
 Peripheral Pump

<https://www.freeadsz.co.za/x-9586-z>



Shimge QB80 0.75kw 230V
 Peripheral Pump

<https://www.freeadsz.co.za/x-9586-z>



Shimge QB80 0.75kw 230V
 Peripheral Pump

<https://www.freeadsz.co.za/x-9586-z>



Shimge QB80 0.75kw 230V
 Peripheral Pump

<https://www.freeadsz.co.za/x-9586-z>



Shimge QB80 0.75kw 230V
 Peripheral Pump

<https://www.freeadsz.co.za/x-9586-z>



Shimge QB80 0.75kw 230V
 Peripheral Pump

<https://www.freeadsz.co.za/x-9586-z>



Shimge QB80 0.75kw 230V
 Peripheral Pump

<https://www.freeadsz.co.za/x-9586-z>



Shimge QB80 0.75kw 230V
 Peripheral Pump

<https://www.freeadsz.co.za/x-9586-z>